

EC4-NH3-100-01

EC4-NH3-100 Ammonia Gas Sensor

EC Sense • Ammonia • Amperometric

The EC Sense EC4-NH3-100 is an electrochemical gas sensor for Ammonia detection, with a 0 – 100 ppm range, 115 nA/ppm $\pm$ 35 nA/ppm sensitivity and T50 < 20 s, T90 < 50 s response. Double-sealed ABS housing at about 8 g with excellent leakage protection — built for long-term industrial field deployment Well suited to industrial safety, leakage detection and emission monitoring, with a designed lifetime of > 2 years.

Specifications

Operating Principle	Amperometric
Bias Voltage	0 mV
Range	0 – 100 ppm
Maximum Overload	200 ppm
Resolution	0.1 ppm (16-bit ADC)
Sensitivity	115 nA/ppm $\pm$ 35 nA/ppm
Response Time	T50 < 20 s, T90 < 50 s
Repeatability	2 %
Linearity	Linear
Zero Current	$\pm$ 300 nA
Recommended Load	100 Ω
Warm-Up Time	< 60 s
Operating Temp.	-30 °C to +55 °C
Operating Humidity	15-95% RH non-condensing
Operating Pressure	800 to 1200 hPa
Storage Temp.	0 °C to 20 °C (Optimum temp. 4 °C to 6 °C)
Housing	ABS
Weight	< 8 g
Long-Term Drift	< 5 %/year
Expected Lifetime	> 2 years
Zero Drift in Clean Air	< 1 ppm
Storage Life	6 months
Warranty	12 months

Key Features

- Detects with high selectivity a wide variety of gases

- Double sealed housing for advanced leakage protection
- Stable zero
- Linear output
- High sensitivity
- nA power consumption
- Wide operation temperature range of -30 °C to +55 °C
- Typical warm-up time in minutes
- RoHS compliant

Typical Applications

- Industrial Safety
- Leakage Detection
- Emission Monitoring
- Sewage/Water Treatment Plant
- Biogas
- Garbage Disposal
- Semiconductor Industry
- Warehouse Logistics Monitoring
- Livestock Farming
- Indoor Air Quality

Calibration & Cross-Sensitivity

Calibrated with Ammonia standard gas. Cross-sensitivity to other gases may exist — see the cross-sensitivity table in the datasheet.